


GROUND WATER PROSPECTS MAP

(PREPARED FROM SATELLITE IMAGE INTERPRETATION WITH LIMITED FIELD CHECKS)







DATA USED: IRS - P6 LISS III FCC dated February 2006, GROUND TRUTH & WELL OBSERVATION during April-May, 2009 & Jan-Feb, 2010, Published Geological maps & Literatures.

Designed & Developed by Hydrogeology Division, NRSC, ISRO

NRSC (ISRO), DEPT. OF SPACE, GOVT. OF INDIA



| MAP UNIT | GEOLOGICAL SEQUENCE / ROCK TYPE | GEOMORPHIC UNIT / LANDFORM | DEPTH TO WATER LEVEL | RECHARGE CONDITIONS | GROUND WATER PROSPECTS | | | | | | RECHARGE STRUCTURES | REMARKS | |
|--|--|---|--|--|---|--|--|---|--|--|--|--|---|
| (HYDROGEOMORPHIC UNIT) REPRESENTED IN THE MAP WITH ALPHANUMERIC CODE (COLOUR INDICATES YIELD RANGE AND HATCHING INDICATE DEPTH RANGE) | (REPRESENTED IN THE MAP WITH NUMERIC CODE) | (REPRESENTED IN THE MAP WITH ALPHABETIC CODE) | PRE / POST- MONSOON (AVERAGE IN METERS) NO. OF WELLS OBSERVED | BASED ON AVAILABILITY OF WATER (RAINFALL & OTHER SOURCES) | AQUIFER MATERIAL LS = LOOSE SEDIMENTS PR = PERMEABLE ROCK FIR = FISSURED ROCK FR = FRACTURED ROCK WR /= WEATHERED ROCK / WM WEATHERED MATERIAL IR = IMPERIVIOUS ROCK | TYPE OF WELLS SUITABLE DW = DUG WELL RW = RING WELL BW = BORE WELL TW = TUBE WELL DBW / = DUG CUM-BORE WELL / DTW DUG CUM-TUBE WELL | DEPTH RANGE OF WELLS (SUGGESTED) MIN - MAX (IN METERS) | YIELD RANGE OF WELLS (EXPECTED) (in LPM or m ³ / day) | HOMOGENEITY IN THE UNIT & SUCCESS RATE OF WELLS (PROBABILITY) VERY HIGH HIGH MODERATE LOW | QUALITY OF WATER POTABLE (P) NON - POTABLE (NP) (INDICATE REASONS IF NON POTABLE) | GROUND WATER IRRIGATED AREA (APPROX . RANGE IN PERCENTAGE) | SUITABLE & PRIORITY PT = PERCOLATION TANK CD = CHECK DAM NB = NALA BUND RW = RECHARGE WELL DT = DESILTING OF TANK RP = RECHARGE PIT SD = SUBSURFACE DYKE RS = RECHARGE SHAFT ST = STORAGE TANK SCM = SOIL CONSERVATION MEASURES | (PROBLEMS / LIMITATIONS) |
| CB111 | Deposits | Channel Bar (CB) | <u>5 - 6</u> 2 | Excellent | LS | TW | 5 -10 m | 400-500 LPM | Very High | Р | 42% | Not Required | Groundwater prospects very high with high recharge potential. Recharge structures not required. |
| PB111 | (Present day mation/Present day (Present day | Point Bar (PB) | 6 1 | Very Good | LS | RW TW | 5 -10 m | 300-400 LPM | Very High | Р | 7% | Not Required | Groundwater prospects very high with high recharge potential. Recharge structures not required. |
| FP111 | Hugli/Bhagirathi Fo | Flood Plain (FP) | <u>5 - 22</u> 104 | Very Good | LS | RW TW | 30 - 40 m | 250-350 LPM | Very High | Р | 93% | Not Required | Groundwater prospects very high with high recharge potential. Recharge structures not required. |
| APY113 | Panskura/ArambaghFormation (Early to Late Holocene) (Early to Late Holocene) (Ilis) (I | Alluvial Plain Younger (APY) | 5.5 - 14.6 DW - 6 HP - 39 | Very Good | LS | DW TW | 10 - 12 m <30 m | 100 - 125 m ³ /day 250 - 300 LPM | Very High | Р | Nil | Not Required | Aquifer is formed of sandy part of alluvium. Recharge structures are not required as good recharge conditions prevail |
| NL13 | ar Holocene) Holocene) Alluvium (Sand, Silt and Clay) | Natural Leeve (NL) | 8.2 - 14.5 DW - 3 HP - 6 | Good to Very Good | LS | DW TW | 10 - 15 m 25 - 30 m | 50 - 75m ³ /day 200 - 250 LPM | High | Р | Nil | Not Required | Aquifer is formed of sandy part of alluvium. Recharge structures are not required as good recharge conditions prevail |
| APO13 | (Sand, Silt and Clay) | Alluvial Plain Older (APO) | 3.5 - 15.4 DW -14 PW - 2 HP - 2 | Good | LS | DW TW | 15 - 20 m 40 - 60 m | 50 - 75 m³/day 150 - 200 LPM | High | Р | Nil | Not Required | Aquifer is formed of sandy part of alluvium. Recharge structures are not required as good recharge conditions prevail |

These are fault / fracture zones, which generally act as conduits for movement of ground water in hard rocks. Along these zones, the yields are significantly higher and wells are likely to be sustainable for longer duration. However, the inferred fractures need to be confirmed by detailed ground surveys.

These are dykes, quartz reefs and pegmatite veins, which generally act as barriers for ground water movement.

N.B.-The depth range and yield range of wells may vary within the unit because of certain inhomogeneities. Fractures/Lineaments which are clearly observed / inferred from the satellite image are indicated on the map. There could be some obscured fractures which also influence the ground water prospects.

Locations of the recharge structures shown in the map are tentative. This map is useful for narrowing down the target zones, and exact location on the ground for wells and recharge structures should be identified based on follow-up ground hydrogeological/geophysical surveys.

| GROUND WATE | R PROSPECTS INFORMATION | HYDROLOGICAL INFORMATION | STRUCTURAL INFORM | IATION | BASE MAP INFORMATION | LOCATION INFORMATION | | |
|---|---|---|--|-------------------------------|---|--|---|--|
| YIELD COLOUR | DEPTH RANGE OF WELLS | DESCRIPTION SYMBOL | DIPS BEDDING | SCHISTOSITY/ FOLIATION SYMBOL | . DESCRIPTION | STATE INDEX | DISTRICT INDEX | |
| RANGE COLOUR CODE OF WELLS | SHALLOW MODERATE DEEP <30 METERS 30 -80 METERS >80 METERS | CANAL / TANK IRRIGATED AREA | GENTLE (<15) | NH - 2 | NATIONAL HIGHWAY | | 1 | |
| > 800 LPM VIOLET | | RIVER / STREAM (with sand) | MODERATE (15 - 45) STEEP (45 - 80) | SH - 9 | STATE HIGHWAY | | a start of | |
| | | WATER BODY / SPRING | SUB - VERTICAL TO VERTICAL (> 80) | X | METALLED ROAD | | | |
| 400 - 800 LPM INDIGO | | CANAL RAIN GUAGE STATION 800 | ANTICLINE / ANTIFORM | ← | OTHER ROAD | INDIA | C D B | |
| 200 - 400 LPM BLUE | | (With average annual rainfall in mm) RECHARGE STRUCTURES SUGGESTED PERCOLATION TANK CHECK DAM | SYNCLINE / SYNFORM | ← | RAILWAY | WEST | E | |
| 100 - 200 LPM GREEN | | NALA BUND RECHARGE WELL DESILTING OF TANK RECHARGE PIT SUBSURFACE DYKE | TREND LINE | | CITY / VILLAGE | BENGAL | A-BIRBHUM B-BARDDHAMAN C-PURULIYA D-BANKURA E-PASCHIM MEDINIPUR | |
| 50 - 100 LPM YELLOW | | SOIL CONSERVATION RECHARGE SHAFT STORAGE TANK WELLS OBSERVED DURING FIELD VISIT YIELD RANGE BORE / YIELD RANGE DUG WEL | | | HABITATIONS : NON - COVERED (NC) PARTIALLY COVERED (PC) | |] | |
| 30 - 50 LPM ORANGE | | N LPM TUBE WELL IN m³/ day RING WE > 800 LPM → 15/70 > 400 m³ / day 0 8/15 400 - 800 LPM → 15/70 200 - 400 m³ / day 0 8/15 | | MAJOR F | BOUNDARY: | BLOCK INDEX | MAPSHEET INDEX | |
| | | 200 - 400 LPM | THRUST TT FRACTURE / LINEAMENT | T | STATE DISTRICT | EA14 | 73M/9 73M/13 79A/ | |
| 20 - 30 LPM BROWN | | 50 - 100 LPM | FRACTURE / LINEAMENT (Inferred) | | вьоск | A16 A16 | 73M/10 73M/14 79A/ | |
| 10 - 20 LPM PINK | | 20 - 30 LPM 15/70 10 - 15 m³/day 8/19 | SHEAR ZONE (Confirmed / Inferred) | s — s/s — s | OTHER INFORMATION | B10 B11 | | |
| Prospects limited to valley portions only | | 10 - 20 LPM | DYKE (Confirmed / Inferred) | DD / DD | Rainfall: 1348mm | A14 LABHPUR B10 AUSGRAM - I A15 NANUR B11 MANGALKOAT | 73M/11 73M/15 79A/3 | |
| (Hills, Plateaus etc.) | | Colour inside well symbol indicates yield range. The figures on the top right hand side of well indicate the depth to water level and depth of well in mete | | Q Q/Q | | A15 NANUR A16 BOLPUR B12 KETUGRAM - I B19 BHATAR | | |
| Run-off zone/ Barrier for G.W. movement | (Inselberg / Ridge / Dyke etc.) | DUG - CUM- BORE WELL HAND PUMP WELL OBSERVATION WELL OF G.W DEPT. / C.G.W.B. | PEGMATITIE VEIN (Confirmed / Inferred) Lithologic contacts are inferred at places & are gradational | | (Source IMD) | | | |
| | REPARED BY | TECHNICAL GUIDANCE & QUALITY CHECK | PARTICIPATING ORGANIZA | | HODOLOGY & PROJECT EXECUTION | SPONSORED BY | | |
| B. STATE COUNCI | CS & REMOTE SENSING CELL L OF SCIENCE AND TECHNOLOGY F SCIENCE AND TECHNOLOGY | इसरो isro NATIONAL REMOTE SENSING CENTRE | SURVEY OF INDI | | IAL REMOTE SENSING CENTRE | RAJIV GANDHI NATIONAL DRINKING WATER MISS (PHASE III B) DEPARTMENT OF DRINKING WATER SUPPLY (DD) | | |
| GOVERNMENT OF WEST BENGAL | | INDIAN SPACE RESEARCH ORGANISATION (ISR | PHED, GOVT. OF WEST | BENGAL INDIAN SE | PACE RESEARCH ORGANISATION (ISRO) | MINISTRY OF RURAL DEVELOPMENT | | |
| | OOR, BIKASH BHAVAN KE, KOLKATA 700 091 | DEPT. OF SPACE, GOVT. OF INDIA BALANAGAR, HYDERABAD - 500 625 | STATE WATER INVESTIGATION DIF P.S.MAPS (LAND RECORD), GOVT | | EPT. OF SPACE, GOVT. OF INDIA LANAGAR, HYDERABAD - 500 625 | GOVERNMENT OF INDIA NEW DELHI | | |